

**Listing of Claims**

1. (Previously amended) A switch which comprises:
  - a. a tilt-sensitive transducer that produces an output signal in response to a user input;
  - b. a differentiator adapted to receive said output signal; and
  - c. means, connected to said differentiator, for performing a first switching function.
2. (Previously amended) A switch as claimed in Claim 1 in which said tilt-sensitive transducer comprises a transducer that produces an output signal proportional to said input.
3. (Previously amended) A switch as claimed in Claim 1 in which said tilt-sensitive transducer comprises a transducer that produces an output signal proportional to a tilting input.
4. (Previously amended) A switch which comprises:
  - a. a transducer that produces an output signal in response to a user input;
  - b. a first differentiator adapted to receive said output signal;
  - c. a second differentiator connected to said first differentiator; and
  - d. means, connected to said second differentiator, for performing a first switching function based on rate-of-change.
5. (Previously amended) A switch as claimed in Claim 4 which further comprises means, connected to said first differentiator, for performing a second switching function.
- 6.-8. (Canceled previously)
9. (Previously amended) A method which comprises:
  - a. producing an output signal in response to a user input;
  - b. differentiating said output signal with respect to time; and
  - c. performing a first switching function in response to said differentiated output signal based on rate-of-change.
10. (Original) A method as claimed in Claim 9 in which said producing step comprises:
  - a. attaching a transducer to a person; and
  - b. body-member actuating said transducer.
11. (Currently amended) A method as claimed in Claim 9 in which:
  - a. said method further comprises differentiating said differentiated output signal a ~~second time~~; and

b. said performing step comprises performing said first switching function in response to said second differentiating step.

12. (Currently amended) A method as claimed in Claim 9 in which:

a. said differentiating step comprises differentiating said differentiated output signal ~~a second time~~; and

b. said method further comprises performing a second switching function in response to said second differentiating step.

13. (Previously amended) A method as claimed in Claim 9 in which said method further comprises:

a. performing said first switching function when said output signal is increasing; and

b. performing a second switching function when said output signal is decreasing.

14. (Previously amended) A method as claimed in Claim 9 in which said method further comprises:

a. performing said first switching function when said output signal is increasing;

b. performing a second switching function when said output signal is decreasing;

and

c. producing a logic output as a function of both of said switching functions.

15. (Previously amended) A method which comprises:

a. body-member tilting a first tilt-sensitive transducer;

b. producing a first output signal proportional to said tilting step;

c. differentiating said first output signal with respect to time; and

d. performing a first switching function in response to said differentiated first output signal.

16. (Previously amended) A method as claimed in Claim 15 in which said method further comprises:

a. body-member tilting a second tilt-sensitive transducer;

b. producing a second output signal proportional to said tilting of said second tilt-sensitive transducer;

c. differentiating said second output signal with respect to time; and

d. performing a logic output as a function of said first and second differentiated output signals.

17. (Previously amended) A method as claimed in Claim 15 in which said performing step comprises performing a switching function that includes momentary contact switching, and said method further comprises:
- a. initiating a sequential plurality of time delays in which one is a window of opportunity;
  - b. refraining from said momentary-contact switching step during a first time delay that follows said initiating step;
  - c. performing said momentary-contact switching step within said window of opportunity that follows said first time delay;
  - d. refraining from said momentary-contact switching step during a second time delay that follows said window of opportunity; and
  - e. initiating operation of a first electrical device subsequent to successful completion of the preceding steps.
18. (Canceled previously)
19. (Previously amended) A method as claimed in Claim 17 in which said method further comprises:
- a. momentary-contact switching during said second time delay; and
  - b. initiating operation of a second electrical device in response to said momentary-contact switching step occurring during said second time delay.
- 20.-30. (Canceled)
31. (Previously amended) A method which comprises:
- a. body-member actuating a transducer;
  - b. producing an output signal proportional to said body-member actuating step; and
  - c. performing a switching function in response to a rate-of-change of said output signal.
32. (Previously amended) A method as claimed in Claim 31 in which:
- a. said producing step comprises producing an output signal that increases and decreases; and
  - b. said performing step comprises performing said switching function whenever said rate-of-change of said increasing output signal reaches a predetermined magnitude.
33. (Previously amended) A method as claimed in Claim 31 in which:

a. said producing step comprises producing an output signal that increases and decreases; and

b. said performing step comprises performing said switching function whenever said rate-of-change of said decreasing output signal reaches a predetermined magnitude.

34. (Previously amended) A method as claimed in Claim 31 in which said method further comprises controlling an apparatus in response to said output signal.

35. (Previously amended) A method as claimed in Claim 31 in which said method further comprises activating control of any apparatus in response to said switching function.

36. (Previously amended) A method as claimed in Claim 76 in which said method further comprises activating control of an apparatus in response to said switching function.

37. (Previously amended) A method as claimed in Claim 76 in which said method further comprises controlling an apparatus in response to said output signal.

38. (Previously amended) A method as claimed in Claim 76 in which said method further comprises activating control of an apparatus in response to said switching function being performed inside a window of opportunity.

39. (Previously amended) A method as claimed in Claim 76 in which said method further comprises:

a. activating control of an apparatus in response to said switching function being performed inside a window of opportunity; and

b. aborting said activating step in response to said switching function being performed outside said window of opportunity.

40. (Previously amended) A method as claimed in Claim 76 in which said method further comprises activating a shut-down function of an apparatus in response to said switching function.

41. (Previously amended) A method as claimed in Claim 76 in which said method further comprises activating a selected one of a first or a second apparatus in response to said switching function.

42. (Currently amended) A method as claimed in Claim 76 in which said method further comprises:

a. activating a selected one of a first or a second apparatus in response to performing said switching function during a window of opportunity; and

b. proportionally controlling a function of said selected apparatus as a function of said ~~proportional~~ output signal.

43. (Previously amended) A method as claimed in Claim 76 in which said method further comprises:

a. activating a selected one of a first or a second apparatus in response to performing said switching function during a window of opportunity;

b. selecting a function of said selected apparatus to be controlled; and

c. said selecting step comprises performing an other switching function.

44. (Previously amended) A method as claimed in Claim 76 in which said method further comprises:

a. activating a selected one of a first or a second apparatus in response to performing said switching function during a window of opportunity;

b. selecting a function of said selected apparatus to be controlled;

c. said selecting step comprises performing an other switching function;

d. controlling said selected function; and

e. said controlling step comprises performing still an other switching function.

45. (Previously amended) A method as claimed in Claim 76 in which said method further comprises:

a. initiating cascading a plurality of task opportunities;

b. selecting a task; and

c. said selecting step comprises performing said switching function.

46. (Previously amended) A method as claimed in Claim 76 in which said method further comprises:

a. initiating cascading a plurality of task opportunities;

b. selecting a task;

c. said selecting step comprises performing said switching function;

d. selectively controlling said task; and

e. said selective controlling step comprises performing an other switching function.

47. (Previously amended) A method as claimed in Claim 76 in which said method further comprises:

a. initiating cascading a plurality of task opportunities; and

- b. said initiating step comprises performing said switching function.
48. (Previously amended) A method as claimed in Claim 76 in which said method further comprises:
- a. initiating cascading a plurality of task opportunities;
  - b. said initiating step comprises performing said switching function;
  - c. selecting a task; and
  - d. said selecting step comprises performing an other switching function.
49. (Previously amended) A method as claimed in Claim 76 in which said method further comprises:
- a. initiating cascading a plurality of task opportunities;
  - b. said initiating step comprises performing said switching function;
  - c. selecting a task;
  - d. said selecting step comprises performing an other switching function;
  - e. selectively controlling said task; and
  - f. said selective controlling step comprises performing still an other switching function.
50. (Previously amended) A method which comprises:
- a. body-member producing first and second proportional output signals; and
  - b. controlling both first and second proportional functions and a switching function of an apparatus in response to said output signals, wherein the switching function is controlled based on a rate-of-change of at least one of said first and second proportional output signals.
51. (Original): A method as claimed in Claim 50 in which said controlling step of said switching function comprises differentiating one of said output signals.
52. (Previously amended) A method as claimed in Claim 50 in which:
- a. said body-member producing step comprises producing output signals that change in both increasing and decreasing directions; and
  - b. said controlling step further comprises controlling said switching function in response to a rate-of-change of one of said output signals that exceeds a predetermined magnitude when said one output signal is changing in a selected one of said directions.
- 53-61. (Canceled previously)
62. (Previously amended) A switch which comprises:

- a. a mechanical-to-electrical tilt-sensitive transducer;
  - b. a differentiator connected to said tilt-sensitive transducer; and
  - c. a comparator connected to said differentiator.
63. (Previously amended) A switch which comprises:
- a. a transducer that produces increasing and decreasing output signals proportional to user actuation in first and second directions; and
  - b. means for producing a switching function in response to a predetermined rate-of-change of said output signal produced by user actuation of said transducer in one of said directions.
- 64-73. (Canceled previously)
74. (Currently amended) A switch as claimed in Claim 63 in which said switch comprises means; for producing a second switching function in response to a predetermined rate-of-change of said output signal produced by user actuation of said transducer in the other of said directions.
75. (Currently amended) A switch as claimed in Claim 63 in which:
- a. said switch comprises means for producing a second switching function in response to a predetermined rate-of-change of said output signal produced by user actuation of said transducer in the other of said directions; and
  - b. said switch further comprises means; for producing a third switching function.
76. (Currently amended) A method which comprises:
- a. producing an output signal;
  - b. selectively performing a switching function in response to said output signal;
  - c. providing a mode of operation in which a rate of change of the output signal is below a threshold rate of change~~preventing variations in said output signal from performing said switching function~~; and
  - d. performing said switching function in response to the a predetermined rate-of-change of said output signal exceeding said threshold rate of change.
77. (Previously added) A method as claimed in Claim 76 in which said producing step comprises actuating an input.
78. (Previously added) A method as claimed in Claim 76 in which said producing step comprises body-member actuating an input.

79. (Currently amended) A method as claimed in Claim 76 ~~in which said performing step further comprises~~ comprising selectively adjusting said threshold ~~predetermined~~ rate-of-change of said output signal.

80. (Previously added) A method as claimed in Claim 76 in which said performing step comprises differentiating said output signal.

81. (Previously added) A method which comprises:

- a. producing an output signal that is a function of an input;
- b. controlling an apparatus in response to said output signal; and
- c. performing a switching function in response to a predetermined rate-of-change of said output signal.

82. (Previously added) A method as claimed in Claim 81 in which said producing step comprises body-member actuating said input.

83. (Previously added) A method as claimed in Claim 81 in which said performing step further comprises selectively adjusting said predetermined rate-of-change of said output signal.

84. (Previously added) A method as claimed in Claim 81 in which said performing step comprises differentiating said output signal.

85. (Previously added) A method which comprises:

- a. performing a body-member gesture;
- b. controlling an output signal in response to said body-member gesture;
- c. maintaining a switch output status irrespective of said body-member gesture; and
- d. changing said switch output status in response to a predetermined velocity of said performing step.

86. (Previously added) A method as claimed in Claim 85 in which said method further comprises controlling an apparatus in response to said body-member gesture.

87. (Previously added) A method as claimed in Claim 85 in which said method further comprises selectively adjusting said predetermined velocity of said performing step.

88. (Previously added) A method as claimed in Claim 85 in which said changing step comprises differentiating said output signal.

89. (Previously added) A method which comprises:

- a. performing a body-member gesture;
- b. controlling an output signal in response to said body-member gesture;



- c. maintaining a switch output status irrespective of said controlling step; and
- d. changing said switch output status in response to a predetermined rate-of-change of said output signal.

90. (Previously added) A method as claimed in Claim 89 in which said method further comprises initiating control of an apparatus in response to said output signal.

91. (Previously added) A method as claimed in Claim 89 in which said method further comprises controlling an apparatus in response to said output signal.

92. (Previously added) A method as claimed in Claim 89 in which:

- a. said performing step comprises increasing and decreasing said output signal; and
- b. said changing step comprises changing said switch output status in response to said increasing output signal.

93. (Previously added) A method as claimed in Claim 89 in which:

- a. said performing step comprises increasing and decreasing said output signal; and
- b. said changing step comprises changing said switch output status in response to said decreasing output signal.

94. (Previously added) A method as claimed in Claim 89 in which:

- a. said performing step comprises producing increasing and decreasing output signals;
- b. said changing step comprises changing said switch output status in response to said increasing output signal; and
- c. said method further comprises performing an other switching function in response to said decreasing output signal.

95. (Previously added) A method as claimed in Claim 89 in which said changing step comprises differentiating said output signal.